

AKH-P 104

Wetting and Dispersing Additive (Solvent Based)

General wetting and dispersing additive for solvent-borne coatings for stabilizing fillers, organic, inorganic, and carbon black pigments in all kinds of resin systems such as two-pack polyurethane and chlorinated polymer systems, two-pack epoxy resin systems, alkyd/amino resin combinations, nitrocellulose systems, solvent-based primer and base-coat of automotive coatings (saturated polyester systems), solvent-based primer and base-coat of coil coatings.

Product Data

Physical Form:	Clear light yellow liquid
Active Content:	55-60%
Density (20 °C):	0.90-1.00 g/ml
Acid Value:	120-130 mg KOH/g

Composition

High molecular weight polycarboxylic acid

Applications

Based on	
Total formulation weight:	0.3-0.5%
Titanium dioxide:	2%
Inorganic pigments:	3-5%
Organic pigments:	4-6%

**Applications >
Recommended for >
Particularly Recommended:**

Coatings > Solvent based systems
> All kinds of resin systems (Alkyd, PU, Epoxy, Polyester, Nitrocellulose)

Special Feature:

Compatible with all resin types



021-88864998
021-88865279
0912-5248514



www.asanchem.com



[@Asankimia](#)
asan.chem
[Asanchem](#)